




A-532



SHAFFER, JOHNSTON, LICHTENWALTER & ASSOCIATES, INC. CONSULTING ENGINEERS

Please reply to: Mansfield

February 26, 1993

SURVEYOR'S DESCRIPTION  
FOR  
OPAL A. MCKENNA

0.480 Acres

Situated in the Township of Washington, County of Richland, State of Ohio and being part of the Southwest Quarter of Section 15, Township 20, Range 18, and being more particularly described as follows:

Commencing at a nail found in the intersection of the south line of said Southwest Quarter and the centerline of Possum Run Road (C.H. 320);

Thence N 15° 14' 00" W, 258.00 feet along said centerline to a P.K. nail set in the southeast corner of a parcel of land conveyed to Opal Almeda McKenna by volume 718, page 228 of Richland County deed records and volume 103, page 215 of Richland County official records;

Thence N 16° 39' 00" W, 268.30 feet and continuing along said centerline also being the east line of said land of Opal Almeda McKenna to a P.K. nail set in the northeast corner of said land, said P.K. nail also being in the southeast corner of a parcel of land conveyed to Opal A. McKenna by deed volume 824, page 157 and official records volume 103, page 213;

Thence N 89° 32' 25" W, 262.54 feet along the south line of said land of Opal A. McKenna as recorded in O.R.V. 103, page 213 to an iron pin set, said iron pin being the true place of beginning;

Thence N 89° 32' 25" W, 329.02 feet and continuing along said south line to an iron pin set;

Thence N 0° 27' 35" E, 84.31 feet to an iron pin set;

Thence S 82° 34' 18" E, 320.72 feet to an iron pin set;


Thence S 12° 46' 06" E, 46.64 feet to the true place of beginning and containing 0.480 acres, more or less, but subject to all legal highways and easements of record.

Grantees, their heirs and assigns do hereby covenant and agree that the parcel of land described in this instrument will not be conveyed by said grantees, heirs and assigns, unless said parcel fronts on a public highway of dedicate street, or is sold together with land fronting on a public street.

Bearings are to an assumed meridian and are used to express angles only.

All iron pins set are 5/8" diameter rod with plastic cap stamped "S.J.L. INC."

According to a survey made in February 1992 by Roger L. Stevens, Ohio Registered Surveyor No. 7052.



*Roger L. Stevens*  
Roger L Stevens  
Registered Surveyor No. 7052

NEW SPLIT  
TAX MAP APPROVED  
EAS INITIAL RLS DATE 2-1-93

A-532