


R. A. KAUFFMAN  
O.R.V. 360, PAGE 928

NORTH



MARIANNA CIRCLE 60' R/W

S 01°19'58" W 180.00'

S 90°00'00" W 115.00'

(LOT #1, BLOCK "B"  
FRANK M. MORITZ S.D.  
"UNRECORDED")

0.475 ACRE

F. HOWDYSELL  
O.R.V. 1687, PAGE 74  
O.R.V. 1687, PAGE 393

N 01°19'58" E 180.00'

THE PLACE OF  
BEGINNING

N 90°00'00" E 115.00'

N 01°19'58" E  
30.00'

THE SE CORNER OF  
THE SE QTR. SEC. 36

CHEW ROAD (T.H. 314)

N 90°00'00" W  
804.96'

BEARINGS ARE BASED ON AN ASSUMED  
MERIDIAN AND ARE INTENDED TO BE  
USED FOR ANGULAR DETERMINATION ONLY

LEGEND

- IRON PIN FOUND
- ⊗ 2" MAG NAIL SPIKE SET
- △ RAILROAD SPIKE SET
- ▲ RAILROAD SPIKE FOUND
- ⊗ 5/8" IRON PIN SET WITH CAP  
STAMPED "CRAIG 8195"



THE SOUTH LINE OF  
THE SE QTR. SEC. 36

*Chad F. Craig*

SURVEY BY: CHAD F. CRAIG P.S. #8195  
for SEILER & CRAIG SURVEYING INC.  
52-1/2 NORTH MAIN STREET  
MANSFIELD, OHIO 44902  
(419) 525-3644  
FAX (419) 525-3696

NEW SURVEY  
OF EXISTING PARCEL  
RICHLAND COUNTY  
TAX MAP OFFICE  
EAK 8-21-09  
INITIAL DATE  
AA-277

SURVEY PLAT FOR	
HENRY	
PART SE QTR. SEC. 36, T-21, R-18 MADISON TOWNSHIP RICHLAND COUNTY, OHIO	
DATE: AUGUST 17, 2009	SCALE: 1"=40'
1493CHEWRD	

**SEILER & CRAIG SURVEYING, INC.**

*Douglas C. Seiler, PS & Chad F. Craig, PS*

*52 1/2 North Main Street*

*Mansfield, Ohio 44902*

*419-525-3644 Fax: 419-525-3696*

*www.seilerandcraig.com*

NEW SURVEY  
OF EXISTING PARCEL  
RICHLAND COUNTY  
TAX MAP OFFICE

EAK 8-21-09  
INITIAL DATE  
AA-277

**SURVEY DESCRIPTION**

PART OF THE SE QUARTER OF SECTION 36  
MADISON TOWNSHIP  
RICHLAND COUNTY, OHIO

Situated in the Township of Madison, County of Richland, State of Ohio and being a part of the Southeast Quarter of Section 36, of Township 21 North, Range 18 West, and being more particularly described as follows:

Commencing at an iron pin found and accepted as marking the southeast corner of said quarter, Thence, North 90 degrees 00 minutes 00 seconds West with the south line of said quarter and the centerline of Chew Road (T.H. 314) a distance of 804.96 feet to a point referenced by an iron pin set on a bearing of North 01 degree 19 minutes 58 seconds East and at a distance of 30.00 feet, Thence, North 01 degree 19 minutes 58 seconds East a distance of 30.00 feet to said reference pin, the place of beginning of the herein described parcel;

Thence, North 01 degree 19 minutes 58 seconds East a distance of 180.00 feet to an iron pin found;

Thence, South 90 degrees 00 minutes 00 seconds West a distance of 115.00 feet to an iron pin found on the east right of way of Marianna Circle;


Thence, South 01 degree 19 minutes 58 seconds West with said east right of way, a distance of 180.00 feet to an iron pin found;

Thence, North 90 degrees 00 minutes 00 seconds East a distance of 115.00 feet to the place of beginning, containing 0.475 acre according to survey by Chad F. Craig P.S. #8195 for Seiler & Craig Surveying, Inc. on August 17, 2009 and subject to all right of ways and easements of record.

Iron pins set are 5/8" rods with caps stamped "CRAIG 8195".

Bearings are based on an assumed meridian, and are intended to be used for angular determination only.

The intent of this instrument is to describe in greater detail the premises transferred by ORV 1200, PG: 776.



*Chad F. Craig*  
Chad F. Craig P.S. #8195  
for Seiler & Craig Surveying, Inc.