

N-198

SURVEY FOR S. ILLINOIS LIMITED PARTNERSHIP

HATHAWAY ROAD (T.H. 331)

N. LINE NE. 1/4 SEC. 31

NW CORNER
NE. 1/4 SEC. 31

K. & S. KIRKENDALL
O.R.V.-873 P.-129

884.71'

S 02°17'06" E

21.33'

60.52'

27.23'

S 84°44'47" E 1387.21'

N 84°44'47" W 1107.44'

S. ILLINOIS LIMITED PARTNERSHIP
O.R.V.-855 P.-814

6.176 AC.

8.68'

N 01°12'34" E
218.16'


S 36°31'56" E
432.33'

443.41'
N 36°54'20" W

376.28'
S 46°15'42" W

LEGEND

- IRON PIN FOUND
- RAILROAD SPIKE FOUND
- △ MAG NAIL FOUND
- IRON PIN SET, 5/8" DIA. ROD WITH PLASTIC CAP STAMPED "STEVENS 7052"



NEW SPLIT
RICHLAND COUNTY
TAX MAP OFFICE

INITIAL: RS DATE: 3-21-01

Roger L. Stevens

Roger L. Stevens, P.S. #7052 Date 3-14-01 SM-1536A

*MONROE TWP. JUNCTION
3-20-2001
William R. [Signature]*

Distances shown hereon are expressed in feet and decimal parts thereof, bearings are to an assumed meridian and are used to express angles only.

CERTIFICATION: I hereby certify that the foregoing survey was prepared from actual field measurements, in accordance with Chapter 4733-37, Ohio Administration Code.

PART OF THE NE. 1/4 OF
SEC. 31, T-22, R-17,
MONROE TWP.,
RICHLAND CO., OHIO.

**SURVEYOR'S DESCRIPTION FOR
S. ILLINOIS LIMITED PARTNERSHIP**

6.176 Acres

Situated in the Township of Monroe, County of Richland, State of Ohio and being part of the Northeast Quarter of Section 31, Township 22, Range 17 and being more particularly described as follows:

Commencing at a railroad spike found in the northwest corner of said Northeast Quarter, said railroad spike also being in the intersection of the centerline of Hathaway Road (T.H. 331) and the centerline of Tucker Road (T.H. 336);

Thence S 02° 17' 06" E, 884.71 feet along the west line of said Northeast Quarter to point being the true place of beginning;

Thence S 84° 44' 47" E, 1,387.21 feet to an iron pin set and passing through an iron pin set at 21.33 feet;

Thence S 36° 31' 56" E, 432.33 feet to an iron pin set;

Thence S 46° 15' 42" W, 376.28 feet to an iron pin set;

Thence N 36° 54' 20" W, 443.41 feet to an iron pin set;

Thence N 01° 12' 34" E, 218.16 feet to a point and passing through an iron pin set at 209.48 feet;


Thence N 84° 44' 47" W, 1,107.44 feet to a point being in the west line of said Northeast Quarter also being in said centerline of Tucker Road and passing through an iron pin set at 1,080.21 feet;

Thence N 02° 17' 06" W, 60.52 along said west line and said centerline of Tucker Road to the true place of beginning, and containing 6.176 acres, more or less, and subject to all legal highways and easements of record.

Bearings are to an assumed meridian and are used to express angles only.

All iron pins set are 5/8" diameter reinforcing rod with plastic cap stamped "STEVENS 7052".

According to a survey made in March 2001 by Roger L. Stevens, Ohio Registered Surveyor No. 7052.



Roger L. Stevens
Roger L. Stevens
Registered Surveyor No. 7052
SM-1536L

NEW SPLIT
RICHLAND COUNTY
TAX MAP OFFICE
INITIAL *RS* DATE *3-21-01*

MEETS
MONROE Twp. 201116
3-20-2001
William R. Anderson

2361116

N-198