



SURVEY FOR
BENJAMIN & CARRIE J. SMITH



LEGEND

- D. DEED
- M. MEASURED
- P. PLAT
- IRON PIN FOUND
- RAILROAD SPIKE FOUND
- ⊗ DRILL HOLE SET IN CONCRETE
- IRON PIN SET, 5/8" DIA. ROD WITH PLASTIC CAP STAMPED "STEVENS 7052"



BEING THE EAST PART OF
LOT 3178 IN THE CITY
OF MANSFIELD, RICHLAND
CO., OHIO.

NEW SURVEY
OF EXISTING PARCEL
RICHLAND COUNTY
TAX MAP OFFICE
EAK 6-11-02
INITIAL DATE



Roger L. Stevens
Roger L. Stevens, P.S. #7052

Date 6-10-02 SM-1545

Distances shown hereon are expressed in feet and decimal parts thereof, bearings are to an assumed meridian and are used to express angles only.

CERTIFICATION: I hereby certify that the foregoing survey was prepared from actual field measurements, in accordance with Chapter 4733-37, Ohio Administration Code.

Roger L. Stevens

June 10, 2002

**SURVEYOR'S DESCRIPTION FOR
BENJAMIN & CARRIE J. SMITH**

EAST PART OF LOT 3178

Situated in the City of Mansfield, County of Richland, State of Ohio and being the east part of lot number 3178 of the consecutively numbered lots in said city as shown in plat volume 4, page 49 and being more particularly described as follows:

Beginning at a drill hole set in concrete in the southeast corner of said lot number 3178, said drill hole also being the west line of Rowland Avenue;

Thence N 89° 33' 33" W, 120.00 feet along the south line of said lot number 3178 to an iron pin set;

Thence N 00° 00' 00" W, 43.80 feet to an iron pin found in the north line of said lot number 3178;

Thence S 89° 33' 33" E, 120.00 feet along said north line of said lot number 3178 to a point being the northeast corner of said lot, said point also being in said west line of Rowland Avenue and being referenced by an iron pin found S 89° 33' 33" E, 0.79 feet from said point;

Thence S 00° 00' 00" E, 43.80 feet along the east line of said lot number 3178 also being along said west line of Rowland Avenue to the **place of beginning** and containing **0.121 acre**, more or less, and subject to all legal highways and easements of record.

Bearings are to an assumed meridian and are used to express angles only.

According to a survey made in June 2002 by Roger L. Stevens, Ohio Registered Surveyor No. 7052.

All iron pins set are 5/8" diameter rod with plastic cap stamped "STEVENS 7052".



Roger L. Stevens
Roger L. Stevens
Registered Surveyor No. 7052
SM-1545

NEW SURVEY
OF EXISTING PARCEL
RICHLAND COUNTY
TAX MAP OFFICE
EAK 6-11-02
INITIAL DATE

P-334