



**G. AUDELLE & KENNETH HESS**

**TO FRANK TAYLOR**

**PART SOUTHWEST QUARTER, SECTION TWENTY SIX (26),  
TOWNSHIP TWENTY-TWO (22), RANGE NINETEEN (19),  
JACKSON TOWNSHIP, RICHLAND COUNTY, OHIO**

**DESCRIPTION:** Being part of the Southwest Quarter of Section Twenty-six (26), Township Twenty-two (22), Range Nineteen (19), Jackson Township, Richland County, Ohio and being more particularly described as follows: Beginning for the same at the intersection of the north line of the Southwest Quarter of Section Twenty-six (26) and the centerline of the Shelby-Mansfield Road (S.R.No. 39); thence S 34°07' W along the centerline of said State Route No. 39 a distance of 242.50 feet to a point; thence S 20°11' E and continuing along the centerline of State Route No. 39 a distance of 183.74 feet to the real point of beginning of the parcel herein described; thence continuing S 20°11' E along the centerline of the Shelby-Mansfield Road a distance of 125.00 feet to a point; thence N 75°18' E a distance of 230.00 feet to an iron pipe; thence N 20°11' W on a line parallel to the Shelby-Mansfield Road a distance of 125.00 feet to an iron pipe; thence S 75°18' W on a line parallel to the southline a distance of 230.00 feet to a point in the centerline of State Route No. 39 which is the real point of beginning and containing 0.66 acres more or less but subject to all legal right-of-ways and easements on record, and all in accordance to a survey made by Fred E. Krocka, Registered Ohio Surveyor No. 3702 on January 15, 1966.

**CERTIFICATION:** I hereby certify that I made the above survey and iron pipe have been placed on all corners.

**ADDENDUM:**

THE ABOVE TANGENT STARTING DISTANCE IS EQUAL TO 537 FEET TO THE SOUTHEAST CORNER OF ABOVE PROPERTY, AS MEASURED ALONG PRESENT CENTERLINE.

*Fred E. Krocka*  
Fred E. Krocka  
Registered Surveyor No. 3702  
January 26, 1966