


0' 200'
SCALE: 1"=200'



PTH 269 1/4 NORTH LINE SEC 11

1204.56' N 89° 38' 46" E

589.37'

17.83 ACRES

S 00° 40' 34" W 220.00'

S 89° 42' 41" W 333.67'
N 89° 42' 41" E 318.71'
667/270 3006'
HOSTETTLER

S 04° 33' 44" W 245.83'

30.11'
59.55'

S 71° 55' 38" W 68.09'
N 66° 13' 56" W 150.04'
845'

S 00° 40' 34" W 344.71'

S 89° 42' 41" W 314.62'
E 1/4 M. LORD
R 1/4 M. JOHNSON
422/376
T. L. WEIR
595/67

N 36° 06' 59" W 244.63'

N 67° 51' 23" W 162.06'

S 86° 15' 57" W 366.12'

20.83'


S.R. 545

13.61± AC.

J. COEY & L. LILLY
869/422

WEST LINE SEC. 11

NORTHWEST QUARTER
SECTION 11, TP 21, RG. 18
MADISON TOWNSHIP
RICHLAND COUNTY
OHIO



LEGEND:

- - 5/8 inch rebar w/cap stamped "PS 7017" set
- - Railroad spike set
- ⊗ - Existing railroad spike
- ⊙ - Existing iron pipe

Steven H. Riedel
Ohio registered surveyor 7016
April 7, 1989