I.P.FD 327.30 N. 4°36'E 0 . . . S. 85°24'E. 59 A. 2011 I.P. FD. S. 29°09'N' OPDYKE 79.59 162.0 ₩ ₩ ∴ 66 スワ 02 PROPERTY SURVEY PT. OF N.W. 1/4 , COLLINS TO I. & H. KING PLYMOUTH TWP. CENTERLINE OF OPDYKE RD.
BASED ON PIPE FOUND ON ONE
ACRE SURVEY NORTH OF SAID
ROAD ADJACENT TO S.R. 98. NOTE -T23, R19 1. P. RESET MON. R IRON PIPE RESET IN SEC. 598.69 N.85°24' W. I.P. RESETY 9 SEPT. 23, 1967 SCALE - 1"= 60" -- IRON PIPE S. 23°48 W. H. 190

Township 23 (Plymouth) of Range 19 and commancing for the same at the interest of Section 7 in section of the content of Range 19 and commancing for the same at the interest of the centerlines of S.R. 98 and podyke Road (T.H.190); thence S. 24 091W. along the centerline of S.R. 98 a distance of 598.59 feet to an iron pin; thence of 598.59 feet to an the true place of beginning for the parcel to be herein conditions for the continuing N.55511W. a distance of 75.0 feet to an iron pipe; thence N. 24 091E. a distance of 327.30 feet to an iron pipe; thence N. 24 091E. a distance of 327.30 feet to an iron pipe; thence N. 24 091E. a distance of 327.30 feet to an iron pipe; thence S.85.24 S. 11ne of the centerline of Opdyke Road measured... parpendicular thereto; thence S.24 091W. a distance of 353.93 feet along an existing porth-south property line, referenced above, to the place of be-

N. 65 5/4

CON. MON.

130.

- PIZ

I hereby certify that a survey of the above described parcel has been made and that iron pipe have been placed on corners of said parcel as indicated above.

CON. R.

Reg. Surveyor No. 4866

KPOOKA, HAUGER & ASSOCIATES SHELEY, OHIO

FENCE -