PLAT OF PROPERTY SURVEY FOR DON GRABER ASSOCIATES, ARCHITECTS, INC. PART OF OUTLOT NO. 28 PART OF THE SOUTHEAST QUARTER OF SECTION FIVE (5) TOWNSHIP TWENTY-TWO (22), RANGE NINETEEN (19) CITY OF SHELBY, SHARON TOWNSHIP, RICHLAND COUNTY, OHIO 3.60 ACRES \$ 85°43'43"E 50.00 DESCRIPTION: BEING A PART OF OUTLOT NO. 28 OF THE CONSECUTIVELY NUMBERED OUTLOTS WITHIN THE CITY OF SHELBY, AND BEING A PART OF THE SOUTHEAST OWARTER OF SECTION FIVE (5), TOWNSHIP TWENTY-TWO (22), RANGE NINETEEN (19), CITY OF SHELBY, SHARON TOWNSHIP, RICHLAND COUNTY, OHIO, AND BEING MORE PARTICULARY DESCRIBED AS FOLLOWS.

BEGINNING FOR THE SAME AT AN IRON PIPE IN THE CENTERLINE OF EAST SMILEY AVENUE WHICH IS THE SOUTHEAST CORNER OF THE SOUTHEAST QUARTER OF SECTION FIVE (5); THENCE N 87°57'OO"W ALONG THE SOUTH LINE OF SAID QUARTER SECTION (CENTERLINE OF EAST SMILEY AVENUE) A DISTANCE OF 660.00 FEET TO A SURVEYOR'S NAIL; THENCE N 8°61'7"E ALONG THE EAST LINE OF OUTLOT NO. 28 A DISTANCE OF 335.02 FEET TO AN IRON PIPE WHICH IS THE REAL POINT OF BEGINNING OF THE PARCEL REREIN DESCRIBED; THENCE N 87'57'OO"W A DISTANCE OF 105.00 FEET TO AN IRON PIPE; THENCE S 4°16'17"W ON A LINE PARALLEL TO THE EAST LINE OF SAID QUARTER SECTION A DISTANCE OF 200.00 FEET TO AN IRON PIPE; THENCE N 87°57'OO"W ON A LINE PARALLEL TO THE SOUTH LINE OF SAID QUARTER SECTION A DISTANCE OF 200.00 FEET TO AN IRON PIPE; THENCE N 87°57'OO"W ON A LINE PARALLEL TO THE SECTION AD DISTANCE OF 200.00 FEET TO AN IRON PIPE; THENCE N 87°57'OO"W ON A LINE PARALLEL TO THE SECTION AD DISTANCE OF 200.00 FEET TO AN IRON PIPE; THENCE N 87°55'OO"W ON A LINE PARALLEL OT THE SECTION AD DISTANCE OF 200.00 FEET TO AN IRON PIPE; THENCE N 8°56' FIT WO N SCALE : 1" = 40' IRON PIPE PLACED IRON PIPE FOUND SURVEYOR'S NAIL 537 9 AN IRON PIPE; THENCE N 87°57 OO W ON A LINE PARALLEL TO THE SOUTH LINE OF SAID QUARTER - SECTION A DISTANCE OF 83.65 FEET TO AN IRON PIPE; THENCE S 4°16'17" W ON A LINE PARALLEL TO THE EAST LINE OF SAID QUARTER - SECTION A DISTANCE OF 135.02 FEET TO A POINT IN THE CENTERLINE OF EAST SMILEY AVENUE, THENCE N 87°57'00" W CENTERLINE OF EAST SMILEY AVENUE; THENCE N87°57'00"W
ALONG THE CENTERLINE OF THE SAID ROAD A DISTANCE OF
50 03-FEET TO A-POINT, THENCE N-4°6'17"E-ON-A-LINEPARALLEL TO THE EAST LINE OF SAID QUARTER-SECTION A
DISTANCE OF 135.02 FEET TO AN IRON PIPE; THENCE
N 87°57'00"W ON-A LINE PARALLEL TO THE SOUTH LINE OF
SAID QUARTER-SECTION A DISTANCE OF 83.65 FEET TO AN
IRON PIPE ON THE EAST LINE OF LOT NO. 1936 OF THE
CONSECUTIVELY NUMBERED LOTS WITHIN THE CITY OF SHELBY;
THENCE N 4°6'17"E ON A LINE PARALLEL TO THE EAST LINE
OF SAID QUARTER-SECTION A DISTANCE OF 537.47 FEET TO
AN IRON PIPE; THENCE S 85°43'43"E A DISTANCE OF 322.09°0
ON THE EAST LINE OF COUTLOT NO. 28; THENCE S 4°16'17"W ALONG
THE EAST LINE OF SAID QUARTER-SECTION A DISTANCE
THE EAST LINE OF SAID QUARTER-SECTION A DISTANCE 3,60 ACRES EASEMENT 105.00 87°57'00" W OUTLOT NO. 28 THE EAST LINE OF SAID QUARTER-SECTION A DISTANCE OF 324.98 FEET TO AN IRON PIPE WHICH IS THE REAL POINT OF BEGINNING AND CONTAINING 3.60 ACRES, MORE OR LESS, BUT SUBJECT TO ALL LEGAL EASEMENTS NOW EGRESS ON RECORD .ol. OFEET TO AN IRON PIPE 200. Ø LINE 18.0 ACRE 50 STREET 41/ 83.65 PREPARED BY: F. E. KROCKA & N 87°57'00" W N 87°57'00" W ASSOCIATES S.E. rocka 1936 l≥ - E THIRD LINE FRED E. KROCKA .02' 16'17' OHIO REGISTERED SURVEYOR NO. 3702 4°I6'I7" 135.02 LO_T DATE: AUGUST 10, 1979 REVISED DATE: MAY 16, 1980 135. Z S Z

50.03

83.65[°]

S. LINE, S.E. 1/4, 765.00

N 87°57'00"W

83.65

50.03

100 45

660.00' 87°57'00"