

THE PLACE OF
BEGINNING

THE NW CORNER OF
THE NW 1/4 SEC. 16

IRON PINS, REF 30'
FROM E OF RD.

W. HANLEY ROAD
CA HWY. 139

V. & G. SCHUCK
0.48 AC
VOL. 730, PG. 152

J & J. BLAKELY
0.616 AC
VOL. 767, PG. 654

1" x 4" IRON IRON PIN
S 89° 06' 16" E 145'

R. A. DECEY
0.51 AC
VOL. 614, PG. 144

MAS CARLINS
0.49 AC
VOL. 613, PG. 516-20

C. A. MAYER 3.457 AC. VOL. 804, PG. 702

2.157 AC.

SURVEYED FOR
TRANSFER

APPROX. LOCATION OF UNDERGROUND GAS LINE 2

ALL IRON PINS SET
BY THIS SURVEY ARE
5/8" Ø WITH PLASTIC
ID CAPS MARKED
"SEILER 4421"

H. DUSH
2.112 AC.
VOL. 829 PG. 241
VOL. 1005, PG. 401

IRON PIN

SURVEY PLAT FOR PROPERTY TRANSFER

CECELIA A. MAYER

PART NW 1/4 SECTION 16, T-20; R-18

WASHINGTON TOWNSHIP

RICHLAND COUNTY, OHIO

DATE: NOV. 7, 1984
DRAWING NO: 641893

SCALE: 1" = 50'
DRAWN BY: JMS

SURVEY BY: JUSTIN A. SEILER
REG. SURVEYOR 4421

